


# DISRUPTING CONCRETE CONSTRUCTION

Digital, sustainable, circular

Prof. Dr. Philippe Block



A collage of three construction-related images. On the left, a worker in a yellow vest stands on a large pile of rubble. In the center, a worker in a hard hat and safety harness is pouring concrete from a large drum into a form. On the right, a tall construction crane is positioned next to a high-rise building under construction, with another crane visible in the background.

Strength through Geometry

Material Effectiveness

Circular Construction

**STRENGTH THROUGH GEOMETRY**



Photo: J. Kurt Schmidt



Photo: Iwan Baan



Photo: Anna Maragkoudaki

A photograph of a modern architectural interior. On the left, a large, textured brick column stands next to a white, angular, geometric structure. In the background, a glass roof allows light to illuminate the space. Several people are standing and walking through the area.

Reduce mass



Photo: Iwan Baan





Photos: James Bellamy





Video: James Bellamy




Photos: James Bellamy / Peter Rich Architects









**-70 %**

A photograph of a modern architectural space. The ceiling and upper walls are constructed from a patterned brick or tile material. The lower walls and floor are made of light-colored stone or concrete. Large glass windows provide a view of a dry, arid landscape with hills in the background.

# Reduce stresses

A photograph of a modern architectural space. The ceiling and upper walls are made of a patterned brick or tile material. The lower walls and floor are made of large, light-colored glass panels. The floor is made of large, irregular stone tiles. The space is open and airy, with a view of the outdoors through the glass walls.

# Reduce carbon footprint



Reduce  
mass





Sha Tin  
沙田

Tsim Sha Tsui & Hong Kong  
尖沙咀及香港


8


3

32B

GET IN LANE  
選定  
行車 線

25.0





A photograph of a modern, multi-level concrete parking garage. The structure features several levels of ramps and flat parking areas, supported by a network of concrete pillars and yellow safety railings. The lighting is dim, creating a moody atmosphere.

> 200 Bn m<sup>2</sup>

by 2050

# MATERIAL EFFECTIVENESS





**-70% concrete  
-90% steel**










Photo: Roman Keller







**3cm**



Photos: Roman Keller



Sha Tin  
沙田



Tsim Sha Tsui & Hong Kong  
尖沙咀及香港

3 3B



GET IN LANE  
選定  
行車線

25.0  
東行



> 40%


-60% concrete  
-80% steel

A black and white photograph showing a construction worker from behind, wearing a red hard hat and safety harness, operating a concrete pump. The worker is positioned on a metal grating over a rebar reinforcement mesh. A thick stream of concrete is being pumped from a hose attached to the pump truck into a large, flat, textured concrete surface. The background shows more of the construction site with other equipment and materials.

7500 cubic metres



1208

A close-up, low-angle shot of a complex, three-dimensional grid of steel reinforcement bars (rebar). The bars are dark grey or black, with visible longitudinal ridges. They intersect at various angles to form a dense, woven pattern that recedes into the distance. The lighting is dramatic, highlighting the texture of the bars and creating strong shadows.

20 km per storey

Germany

# From Zurich to Brussels

7 h 16 min  
658 km


6 h 56 min  
625 km

7 h 11 min  
669 km

STRUCTURAL  
GEOMETRY

LOW CARBON  
CONCRETE

$$GWP = \sum_i ( M_i \times ECC_i )$$



GWP = global warming potential (kgCO<sub>2</sub>e/m<sup>2</sup>)

M = mass (kg/m<sup>2</sup>)

ECC = embodied carbon coefficient (kgCO<sub>2</sub>e/kg)

## STRENGTH THROUGH GEOMETRY    X    LOW-CARBON MATERIAL



Less mass <sup>1</sup>

Lower stresses <sup>2</sup>

Less clinker <sup>3</sup>

**- 60%**

**- 20%**

**- 67%**

→

**- 90%**



→

**- 80%**


<sup>1</sup> Compared to RC floor slab

<sup>2</sup> C30/37 → C16/20


<sup>3</sup> CEM I /OPC → CEM III+




**-85% GWP**




**50% GWP**  
**100% M**



**20**  
~~15%~~ **GWP**  
**33% M**



**50% GWP**  
**100% M**




**15% GWP**  
**33% M**    **\$\$\$**

# CIRCULAR CONSTRUCTION




Photo: Juney Lee



# Rippmann Floor System

Prefabricated  
=  
Fast & safe


Dry-assembled  
=  
Easy deconstruction



Low strength  
=  
Low-carbon concrete

Material separation  
=  
Low-carbon concrete

Fully unreinforced  
=  
Durability



# VAULTED

<https://vaulted-floors.com/>

Spin-off | **ETH** zürich









aluexbeams

LANDISBAU






# Fire safety



Load bearing  
(R)

NFT1  
943.00E+00  
500.00E+00  
471.87E+00  
443.75E+00  
415.63E+00  
388.51E+00  
339.00E+00  
321.88E+00  
273.33E+00  
216.67E+00  
168.33E+00  
120.00E+00  
19.97E+00





Separation  
(E)


Insulation  
(I)



# Acoustic performance










© Gigon / Guyer Architects



# COMPAS

<https://compas.dev/>

```
def smooth_mesh(mesh, lmin, lmax, f  
    if callback:  
        if not callable(callback):  
            raise Exception('Callback is not a function')  
        callback(mesh, lmin, lmax)  
  
    mesh = mesh.copy()  
    mesh.edges = mesh.edges[fixed]  
    mesh.edges = mesh.edges[~mesh.edges.isin(fixed).values]  
  
    for i in range(lmin, lmax+1):  
        mesh = smooth_mesh_length(mesh, i, i+1, f)  
  
    if callback:  
        if not callable(callback):  
            raise Exception('Callback is not a function')  
        callback(mesh, lmin, lmax)  
  
    return mesh
```



## Spatial Structure

- Default Project (IfcProject)
  - Default Site (IfcSite)
    - Default Building (IfcBuilding)
      - Default Storey (IfcBuildingStorey)
        - RFS (IfcSlab)
          - platform (IfcBuildingElementProxy)
          - H20\_upper (IfcBeam)
          - indents (IfcBuildingElementProxy)
          - side boards (IfcWall)
          - foam\_top (IfcBuildingElementProxy)
          - foam (IfcBuildingElementProxy)
          - H20\_lower (IfcBeam)
          - props\_top (IfcColumn)
          - stied\_top (IfcColumn)
          - foam\_bottom (IfcBuildingElementProxy)
          - lid\_top (IfcBuildingElementProxy)
          - beto (IfcBuildingElementProxy)
          - props\_bottom (IfcColumn)

## Info

Attributes Properties

name	value
GlobalId	3DMsVq1Y98PeoG3T98OMBQ
OwnerHistory	None
Name	RFS
Description	None
ObjectType	None
ObjectPlacement	None
Representation	None
Tag	None
PredefinedType	None

## Explode


scale

55

fps: 4

> 40%





Structural geometry

>

Reduction mass

Funicular form

>

Reduction emission

Digital fabrication

>

Reduction waste

Discrete masonry

>

Circular construction

Integrated AEFC approach

>

Economy & Productivity



<https://block.arch.ethz.ch>

<https://vaulted-floors.com>

<https://compas.dev>



@blockresearchgroup  
@philippe\_block



<https://block.arch.ethz.ch>

<https://vaulted-floors.com>

<https://compas.dev>



@blockresearchgroup  
@philippe\_block